

RUBBOSEAL TECHNICAL DATA SHEET

RUBBOSEAL is in single pack high quality Butyl Rubber paint for **WATER PROOFING** and **ANTI-CORROSIVE**. It does not contain BITUMIN.

Features

- Fast drying.
- Good Elasticity.
- Excellent Adhesion.
- All weather resistance.
- Recommended for use in industrial environment.

Technical Data

Color: Black and Dark Grey.

Gloss: Matt Finish.

Volume Solids: Approx.45%

Recommended dft / coat: 30-35 microns.

Theoretical covering capacity: 8.00 m²/l @30 microns dft (Spray Application)
2.5 m²/l @ 80 microns dft (Brush Application)

Drying time @ 30°C: Surface dry: 15 minutes.
Hard dry/Curing: 24-48 hours.

Shelf life (cool & dry place): At least 12 months.

Stability: To be used within 3-5 hours after opening the container.

Directions for use

Surface Preparation

- Surface should be dry and cleaned properly and it should be free from all the contamination. The surface should be sufficiently roughened prior to painting.
- Surface temperature must be at least 3°C above dew point but not above 50°C.

Application

Brush/Roller

Recommended thinner: T-101 / Turpentine

Volume of thinner: 0.2 – 0.5 %

Painting Brush: Size 4 No.

Air Spray

Recommended thinner: T-101

Volume of thinner: 200-300%

Air Spray: HVLP Gun

Nozzle orifice: 0.5 -1.00 mm

Storage & Packaging

Storage: Store in a cool & dry place. Store in accordance with local regulations.

Packaging: 1/4/20 Litres.

Safety Information:

As a general safety measure, inhalation of solvent vapors or paint mist and contact of liquid paint with skin & eyes, should be avoided. Forced ventilation should be provided when applying paint in confined spaces or stagnant air. Even when ventilation is provided, respiratory, skin and eye protection are always recommended when spraying paint.

Please refer our material safety data sheet prior to using the product.

Disclaimer

To the best of our knowledge the information provided herein is true and accurate at the date of issuance. Since we have no control over the quality or condition of the substrate or the various factors affecting the use and application of the product, we do not accept any responsibility or liability arising out of use of the product. The company reserves the right to modify data contained herein without prior notice. Any change in data would be normally be followed by issue of a new data sheet. The user should check with the nearest sales office or distributor of the company and confirm the validity of the information, prior to using the product.